APD Series Bench/Floor Scale

As of: Tuesday, December 23, 2025



Standard Features

- Mobile weight indicator with adjustable inclination, ABS case and 1m connection cable. Backlit LCD display with 6 high contrast 25 mm digits and icons for showing the active functions. Functional waterproof 5-key keypad.
- Aluminium load cell functioning.
- Easy to clean stainless steel body, suitable for use in harsh environments.
- Stainless steel 365x235mm plate.
- Level, adjustable feet, and lateral carrying handles.
- Alimentation through built-in rechargeable battery (about 80h battery life) battery charger is included (to not use as power adaptor).
- Packaging: 550x500x290mm size - approximate weight of 9,7kg.

- Upon request:
  - ACCREDIA calibration with issuing of relative certificate;
  - CE-M approval.

Bench scale with weight indicator designed which can either be mounted attached to the platform or it can be mobile for remote positioning, thanks to the stretchable cable. Available also CE-M approved for legal for trade use.

Functions

- Weight totalization in loading or in unloading, manual or automatic;
- lb/kg conversion;
- tare;
- auto switch-off;
- backlight control;
- battery levels warning;
- zeroing.

Available versions

Code	l x w x h (mm)	Max (kg)	d (g)	M 2R (g)*	d HR (g)*
APD15-1	365x235	6/15	2/5	2/5	0,5
APD30-1	365x235	15/30	5/10	5/10	1
APD1230-1	365x235	12/30	2/5	2/5	--

(*) CE-M divisions are obtainable only with the relative options. HR divisions (not available for approved versions) needs the THR option.

Parts

Part #	Description
Available Versions	
APD15-1	Portable bench scale with 6/15 kg dual range capacity, 2/5 g division, stainless steel structure and plate.
APD30-1	Portable bench scale with 15/30 kg dual interval capacity, 5/10 g division, stainless steel structure and plate.
APD1230-1	Portable bench scale with 12/30 kg dual interval capacity, 2/5 g division, stainless steel structure and plate.

Options

Part #	Description
International Power Plugs	
UK-V3	Version with UK charger.
US-V3	Version with US charger.
AUS-V3	Version with AU charger.
Calibration Service (ACCREDIA/DAKKS) Only at Time of Order	
CT4	ISO 17025 calibration certificate from 6 to 60 kg for single scale/platform. For precision and industrial scales, crane scales. The certificate is provided in digital format (pdf) and sent by e-mail.
Approval for Sale to Third Parties	
ECEM2	Multi-range 3000+3000e legal for trade approval, for single platform/scale. NOTE: Depending on the product, the ECEM approval service may require DINICAL calibration service. Check to see if DINICAL is in the product options.
ECEMDOC	Printed EU declaration of conformity, EU certificate of verification, test certificate and metrological book (free download from our website, only for approved CE-M products). NET €.
High Resolution (d HR) (only at time of order)	
THR	High Resolution (HR) model.
Storing Weighments	
SWM	"WeiMonitor" PC program to monitor and record in real time weighs performed on the connected scale (the price is intended for the license to manage one scale).
Communication Interfaces	
BLTH-3	RS232/Bluetooth Classic 3.0 conversion card complete with AMP cable and integrated antenna.
Connection Cables	
RSCBUSB-1	USB PC/RS232 converter cable, l=1,5m. USB/RJ11 connector.